


Features

Tri-state operation
Tight Symmetry (45% – 55%) available
Operational Voltage: 1.8, 2.5, 3.3V
Tape & Reel: 1K / 2K / 3K / 5K pcs. per reel
Ultra- miniature pkg. 1.6x1.2x0.7 mm Ceramic SMD.
RoHS Compliant Product


Typical Applications

Mobile Phone, 5G Station,
AIoT, Meta, CharGPT,
WiLAN / WiMAX, HDTV

Crystal Oscillator
1.6 x 1.2 x 0.7mm Ceramic SMD
1.0MHz – 80.0MHz



Outlines & Dimensions (mm)



Electrical Specifications

Parameter	Specifications			Unit
Frequency Range	1.0 ~ 80.0			MHz
Frequency Tolerance (@25°C)	±10, ±20, ±30, ±50, ±100			ppm
Supply Voltage	3.3 ± 0.33, 2.5 ± 0.25, 1.8 ± 0.18			V _{DD}
Current Consumption *	1 (typ.) / 40MHz@3V			mA
Output	CMOS			
Symmetry	40/60, 45/55			%
Tri-State (Input to Pin 1)				
Output High (Logic "1")	Output Enabled			
Output Low (Logic "0")	Output Disabled (High Impedance Output)			
Storage Temp. Range	-40 ~ +85			°C
Operating Temp. Range	-10 ~ +60	-20 ~ +70	-40 ~ +85	
Frequency vs. Temp. (@25°C)	±10,	±20	±30	ppm
	±20	±30	±50	
	±30	±50	±100	
	±50	±100	-	

* Frequency & Supply Voltage dependant

Bypass capacitor should be connected between V_{DD} & Gnd for stable operation.



Specifications subject to change without notice.



CALTRON DEVICE LTD.

<http://www.caltron.com.hk> (852)2422-3407 sales@caltron.com.hk